

MATERIAL SAFETY DATA SHEET
OSHA Hazard Communication
Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed date: 2/17/98 at 11:58:0

PRODUCT NAME: **WILLIAMSBURG HANDMADE OIL COLORS**
PRODUCT COLOR: **NICKEL ANTIMONY COLORS**
PRODUCT NUMBER: **SEE LIST**
REGULATORY STATUS: **CONFORMS TO ASTM D-4236, LHAMA AND FHSA**

SECTION I MANUFACTURER'S NAME AND LOCATION
COMPANY NAME **GOLDEN ARTIST COLORS, INC**
ADDRESS **188 BELL ROAD**
CITY, STATE, ZIP **NEW BERLIN NY USA 13411**
Contact **BEN GAVETT** Title **DIRECTOR OF REGULATORY AFFAIRS**
INFO TEL NO. **1-607-847-6154**
EMERGENCY TEL NO. **1-607-847-6154**
Preparation Date: **05/21/10** REV.#

SECTION II HAZARDOUS INGREDIENTS/ IDENTITY/ STANDARDS/ CONTENT INFORMATION

Ingredient Listing	CAS No.	OSHA PEL	ACGIH TLV	STEL	% COMP
Oil Base Medium	mixture	n/l	n/l	n/l	<70.00
Nickel metal as Ni	7440-02-0	1mg/m3	1mg/m3	n/l	<50.00
Antimony & Compounds	7440-36-0	0.5mg/m3	0.5mg/m3	n/l	<50.00

The other ingredients in the oil base medium are judged to be non-hazardous and are regarded as trade secrets

SECTION III PHYSICAL/ CHEMICAL CHARACTERISTICS

Boiling Point **n/a** Deg. F (Cel.) Spec Grav **.930 @ 68 F.**
Melting Point **n/a** Deg. F (Cel.) (H29=1).
Vapor Pressure **n/a** Vapor density **n/a**
Evaporation Rate **n/a** Water Solubility **n/a**
Odor **n/a** Appearance **Yellow Viscous oil paint**

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point **>200 F.** Deg. F.(Cel) Flash Pt. Method **unkwn**
Lower Flam Limit **n/l** % Upper Flam. Limit **n/l**
Exting. Medium **Regular foam, water fog, carbon dioxide, dry chemical.**
Specialized Fire Fighting Proc. **Wear a self contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.**
Unusual Fire & Explosion Hazard **May form: acrolein, carbon dioxide and carbon monoxide, various hydrocarbons.**

SECTION V**REACTIVITY DATA**

(Unstable) Conditions **None known**
Stable (yes/no) **yes** to avoid
(Stable)
Incompat (Avoid) **None**
Haz. Decomp. (y/n) **no** Haz. Polym. (yes/no) **no**
Cond to Avoid **none**

Confirm all information prior to use

Abbreviations:	Not Applicable N/A..	Not Flammable NIF	Ceiling Value	C
	Not Known N/K		Not Determined	N/D
	Respirable Fraction R		Not Listed	N/L
Permissible Exposure Limit PEL			Unknown	UNKWN
			ACGIH Threshold Limit Value	

TLV

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.

SECTION VI HEALTH HAZARD DATARoutes of Entry: Inhalation **yes**Skin **Yes**Ingest, **Yes**

Health Hazards

Potential cancer hazard! IARC considers nickel compounds to be carcinogenic to humans.NTP Carcinogen **NO**IARC Carcinogen **Yes**OSHA Carcinogen **No**

Signs/Symptoms of Exposure

Irritation of the eyes, skin and respiratory tract

Medical Conditions to Avoid

Respiratory and skin disorders aggravated by dust.

First Aid

On contact with eyes, flush eyes with plenty of water for at least fifteen minutes. Call a physician. On skin contact, wash thoroughly with soap and water.

SECTION VII**PRECAUTIONS FOR SAFE HANDLING AND USE**

spill

**Absorb liquid on vermiculite, floor absorbent or other absorbent material
Disposal should be in accordance with all applicable local, state and federal regulations.**

Waste Disp

Precautions

Do not store near heat. Keep cool. Avoid contact with skin or eyes. Do not apply by spraying. Avoid dust. Avoid prolonged and repeated skin contact.

Other Precautions

None known

SECTION VIII**CONTROL MEASURES**

Resp Protect

Normally not needed.

Local Exhaust

Normally not needed

Spec Local Exh

Normally not needed

Mech Exhaust

Normally not needed

Other Mech Exhaust	Normally not needed
Protect Gloves	Wear gloves or use barrier creams to protect skin.
Eye Protect	Normally not needed
Protect Clothing	Freshly-laundered artist's smock.
Work Practices	Wash hands and face after use.

LABEL STATEMENTS FOR WILLIAMSBURG - HANDMADE OIL COLORS

Acute Toxicity **None**

Chronic Toxicity **None**

CALIFORNIA PROP 65

WARNING STATEMENT

WARNING' This product contains a chemical known to the State of California to cause Cancer.

Certification Assurance **Conforms to ASTM D-4236**

Children's Hazard Warning **KEEP OUT OF THE REACH OF CHILDREN.**

Confirm all information prior to use

Abbreviations:	Not Applicable N/A..	Not Flammable NIF	Ceiling Value	C
	Not Known N/K		Not Determined	N/D
	Respirable Fraction R		Not Listed	N/L
Permissible Exposure Limit PEL			Unknown	UNKWN
TLV			ACGIH Threshold Limit Value	

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.